



10 Year Limited Warranty – Patriot

U.S. Rubber Recycling, Inc. (U.S. Rubber) warrants to the first purchaser for use that Patriot is free from defects in material and shall not delaminate due to substrate moisture vapor for a period of ten (10) years from the date of invoice, provided that it was used for the interior installation of approved flooring products over properly prepared substrates (see the current technical data sheet for complete details).

Substrates shall be properly prepared per ASTM F710, have no visible or standing moisture, have an intact moisture vapor retarder per ASTM E1745, and be without hydrostatic pressure. The installation must be performed following both the flooring manufacturer's and Taylor Adhesives' guidelines. Please visit www.tayloradhesives.com for the latest application instructions.

If an installation failure occurs as a direct result of the use of defective Patriot, or delamination due to elevated moisture vapor or pH, U.S. Rubber will pay for equivalent floor covering, provide replacement Patriot, and pay for reasonable labor costs to repair or replace the failed portion of the installation as determined by U.S. Rubber at its sole discretion. This limited warranty applies only to adhesive related bond failures. U.S. Rubber does not warrant variables it has no control over such as the quantity of adhesive used, the workmanship of the installer, the condition of the subfloor, the stability of the flooring product and its suitability for installation on the affected jobsite, or any other conditions that might affect the installation.

U.S. Rubber reserves the right as deemed necessary to inspect any claim for cause. This warranty is null and void if U.S. Rubber is prevented from exercising this right. Any repairs done prior to inspection by a U.S. Rubber representative will void this warranty. U.S. Rubber makes no implied warranty of merchantability or fitness for any particular purpose. ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, ARE EXCLUDED.