



**TAYLOR**  
Phone: 800.868.4583  
Fax: 706.712.0909  
800 College Drive  
Dalton, GA 30720

July 22, 2021

Jerry Wilkinson  
Vice President of Sales  
U.S. Rubber Recycling, Inc.

RE: U.S. Rubber Patriot Transitional Pressure Sensitive adhesive

Jerry,

W.F. Taylor LLC recommends and warrants the U.S. Rubber Patriot TPS for the installation of a variety of flooring products designed for installation with a PSA. U.S. Rubber Patriot is plasticizer resistant and can be used to install LVT, LVP, VCT, Fiberglass Backed Sheet Vinyl, Rubber Underlayment, Rubber Sheet & Tile and Sheet Vinyl to name a few. U.S. Rubber Patriot is recommended and warranted for applications with high moisture RH and MVER over new concrete substrates with intact vapor barriers. This warranty is for a period of ten years and covers installations in residential, commercial, and multi-family applications. U.S. Rubber Patriot is a high moisture tolerance adhesive capable of withstanding concrete substrate moisture up to 12 lbs. per ASTM F 1869 or 99% RH per ASTM F 2170 with pH ranges up to 12. **U.S. Rubber Patriot is a high moisture tolerance adhesive not a moisture barrier and will not protect the flooring from moisture damage. Please contact the flooring manufacturer for maximum allowable moisture and pH ranges.** The installation must be performed following both the flooring manufactures and Taylor's guidelines. Please visit [wftaylor.com](http://wftaylor.com) for the latest product information and application instructions.

If an installation failure occurs as a direct result of the use of defective adhesive, Taylor will pay for equivalent floor covering and adhesive materials and for reasonable labor costs to repair or replace the failed portion of the installation as determined by Taylor at its sole discretion. This warranty applies only to the adhesive related bond failures. However, W.F. Taylor cannot warrant those variables over which our company has no control. Factors such as the quantity of the adhesive used, the workmanship of the installer, the condition of the subfloor, the stability of the flooring product or its suitability for the installation on the particular job, excessive moisture or alkalinity, or any other conditions that might affect the installation.

W. F. Taylor reserves the right to inspect the cause for any claim as deemed necessary or this warranty is null & void. Any repairs done prior to inspection by a Taylor representative voids any warranty. This warranty is non-transferable.

Sincerely,

*Gary Scheidker*

Gary Scheidker  
Director of Technical Services

 **TAYLOR™**