



## Product Specifications

Survivor™ SportFloor is a collection of premium, competitive rubber flooring products, which includes rolls and tiles.

**EPDM Content:** 10% Color Fleck Single Color

**Design:** Continuous Rolls of Rubber Flooring and Tiles, which include Square, Interlocking, Eco-Lock and Mega

**Packaged:** Wrapped Rolls, Palletized

### DIMENSIONS

Thickness	Pounds per sq ft	Roll Lengths (48" wide)
3mm (1/8")	0.8	75'
4mm (5/32")	0.95	75'
6mm (1/4")	1.6	75'
8mm (5/16")	1.9	50'
9mm (3/8")	2.2	50'
12mm (1/2")	2.8	50'
18mm (3/4")	4.4	15'

### PRODUCT STANDARDS FOR ROLLS AND TILES

Item	Standard	Rating for Rolls and Tiles*
Density	D3676	68.3lbs/cubic foot
Tensile Strength	ASTM D412	265 psi
Tear Resistance	ASTM D413	Average Elongation at break 1.52
Hardness	D2240	Shore A 65 +/- 5
Slip Resistance	D C1028	Friction Coefficient .084-.090
Abrasion	D4060	2,000 cycles taber abraser 1kg, 0.329g - 0.35g loss
Flammability	ASTM E648	Critical Radiant Flux <0.10W/cm2
Chemicals	N/A	Resistant to most acids and chlorine
Volatile Organic Compounds	CDPH v1.2	<.05mg/m3

\*Rolls are 3mm, 4mm, 6mm, 8mm, 9mm, and 12mm. Eco-Lock Tiles are 6mm and 8mm. Square and Interlocking Tiles are 6mm, 8mm, 9mm and 12mm.



www.usrubber.com  
 info@usrubber.com  
 (833) US RUBBER (877-8223)